
RT-6100 Quick Reference Guide



Side Menu

The side menu displayed by pressing on the measurement screen enables operations other than measurement.

ID

Age

Data list

Range of Clear Vision

Ch.Lamp Link off,

About Eve

Image

OPD 💿 🕨

Near chart

Amsler grid

L


Level

Vision through lens

Setting

R

<Close>



Used to enter the patient ID.

<Age>

Used to enter the patient's age.

<Data list>

Displays the measurement data – list.

<Range of Clear Vision>

Displays the clear vision range check screen.

<[+] , [-]>

Selects a cylinder reading sign from plus and minus.

<Lamp off>

Turns off the chart lamp, touch screen backlight, and near point lamp. To turn them on, press any button.

<Ch. Lamp>

Turns the chart lamp on or off.

<About Eye>

Displays the Refraction diagram list screen.

<Near chart>

Displays the near chart screen.

Amsler grid > Displays the Amsler grid screen.

<[R] , [L]>

LM

0.00 - 0.00

135

<Setting>

Displays OPD images of the right or left eye (only when data is imported).

<Near Lamp>

Turns on or off the near point lamp.

<Level>

Used to align the chart height to the patient's eye level (only when the SSC-370 is connected).

<Link off>

Disables auxiliary lenses or mode (SPH, CYL, AXIS) from being automatically switched when the chart is changed.

<Vision through lens>


Displays the vision image screen.

180° 45° 90° 1

Displays the menu screen.

<Image>

Displays images saved on the SD card.



NIDEK